

DECLARATION OF **PERFORMANCE**

DECLARATION NUMBER
TEC36CPR2013 +A1:2016

TTSPS 150MM-250MM TTSPSCJ 150MM

TecTies Ltd hereby declares that Safety Plain Safety Ties TTSPS 150mm-250mm & TTSPSCJ 150mm are in conformity with the provisions of **ZA Annex of EN 845—1 : 2013+A1:2016**

Intended Use

Symmetrical Shear Tie for connecting two leaves of a masonry wall.

Notified Body

Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ **Tel.** +44 (0)1782 764428

Notified Body Number 1289

Underwritten by TZUS - Prague

Notified Body Number 1020

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

Essential Characteristics

Compressive Load Capacity	2610N
Tensile Load Capacity	1950N
Displacement at 1/3 Load - Tensile	0.65mm
Water Shedding Capability	Resistant
Durability - Material Reference 3	Austenitic Stainless Steel
Durability - Wire Grade	304 18/8 comp. to BS EN 10088/1
Embedment Depth	62.5mm
Minimum Mortar Designation	(iv)
Minimum Mortar Joint Width	10mm
Recommended Spacing	As required

Signed for and on behalf of the manufacturer by:



Bob Wood, Tecties Managing Director, on 14th September 2023



visit **www.tecties.co.uk** for more information or call **01663 749361**