

DECLARATION NUMBER  
**TEC34CPR2013 +A1:2016**

## TTCH 100MM-200MM

TecTies Ltd hereby declares that 25/14 Channel Ties TTCH are in conformity with the provisions of **ZA Annex of EN 845—1 : 2013+A1:2016**

#### Intended Use

Asymmetrical and Movement Tolerant Shear Ties for use with 25/14Channel to connect a new masonry leaf to an existing structure

#### Notified Body

Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ Tel. +44 (0)1782 764428

**Notified Body Number** 1289

**Underwritten by** TZUS – Prague

**Notified Body Number** 1020

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

### Essential Characteristics

Compressive Load Capacity	1160N
Tensile Load Capacity	1150N
Displacement at 1/3 Load - Compression	0.43mm
Displacement at 1/3 Load - Tensile	1.38mm
Water Shedding Capability	Resistant
Durability - Material Reference 3	Austenitic Stainless Steel
Durability - Wire Grade	304 18/8 comp. to BS EN 10088/1
Embedment Depth	62.5mm
Minimum Mortar Designation	(iv)
Minimum Mortar Joint Width	10mm
Recommended Spacing	As required





Signed for and on behalf of the manufacturer by:



Bob Wood, Tecties Managing Director,  
 on 14th September 2023



visit **www.tecties.co.uk** for more information or call **01663 749361**

 Tecties, Hague Bar Works, Hague Bar, New Mills SK22 3AT  
 T: 01663 749361  F: 01663 747897  E: sales@tecties.co.uk