

MOVEMENT & RESTRAINT FIXINGS

All TecTies Movement and Restraint Fixings are independently tested at Lucideon Ltd, a UKAS accredited laboratory NO 0013, to the requirements in Standard BS EN 845-1:2003.

Underwritten by TZUS – Prague Notified Body Number 1020

MOVEMENT FIXINGS

These products are designed to provide restraint in one direction and movement to allow for horizontal expansion and contraction. The Debonding Sleeve is located over the embedment detail to allow the tie to move.

TTSSPE (Stainless Steel)
TTGSPE (Galvanised)

Standard Sizes		
150mm	225mm	
175mm	250mm	
200mm		

TTSPS (Stainless Steel)
TTSPSCJ 150mm

Standard Sizes
200mm
225mm
250mm

Special sizes can be manufactured to order.

TTDS

Debonding Sleeve

100mm x 20mm

150mm x 20mm

Ties can be supplied with or without sleeve.

TTSSPE Test Results BS EN 845-1: 2013 + A1 2016

	Mean Load Capacity	Displacement at 1/3 load
Shear	2610N	NPD
Tension	1950N	0.65mm

Projection

Special sizes can be manufactured to order.





Special sizes can be manufactured to order.

Standard Sizes
100mm Projection

125mm Projection 150mm Projection

175mm Projection

200mm Projection

RESTRAINT FIXINGS

Typical usages are in areas where masonry is restrained to Steelwork columns and in long spans of brickwork where movement joints are required. of the Building Regulations for Type B in external walls.

Clasp Ties

This product is designed to restrain masonry to vertical structures. Three holes for screwfix, bolting or shotfiring and safety end detail for embedment. Manufactured in Stainless steel.

	Mean Load Capacity	Displacement at 1/3 load
Tension	8900N	1.13mm





visit www.tecties.co.uk for more information or call 01663 749361



