

DECLARATION NUMBER  
**TEC35CPR2013 +A1:2016**

# TTSU 230MM

TecTies Ltd hereby declares that Sliding Anchor Ties TTSU 230mm are in conformity with the provisions of **ZA Annex of EN 845—1 : 2013+A1:2016**

**Intended Use**

Symmetrical Cavity Wall Ties with a v drip and a slot in the middle. For use with a sliding anchor column, designed to fit in a cavity and restrain the masonry leaf to overhead structures.

**Suitable for**

cavities up to 105mm

**Notified Body**

Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ Tel. +44 (0)1782 764428

**Notified Body Number** 1289

**Underwritten by** TZUS – Prague

**Notified Body Number** 1020

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

## Essential Characteristics

Compressive Load Capacity	4240N
Tensile Load Capacity (central hole)	2510N
Displacement at 1/3 Load - Compression	0.46mm
Displacement at 1/3 Load - Tensile	0.18mm
Water Shedding Capability	Resistant
Durability - Material Reference 3	Austenitic Stainless Steel
Durability - Wire Grade	304 18/8 comp. to BS EN 10088/1
Embedment Depth	62.5mm
Minimum Mortar Designation	(iv)
Minimum Mortar Joint Width	10mm
Recommended Spacing	As required

Signed for and on behalf of the manufacturer by:



Bob Wood, Tecties Managing Director,  
 on 14th September 2023



visit **www.tecties.co.uk** for more information or call **01663 749361**

📍 Tecties, Hague Bar Works, Hague Bar, New Mills SK22 3AT  
 📞 T: 01663 749361 F: 01663 747897 🌐 E: sales@tecties.co.uk